

DECLARATION OF PERFORMANCE

No N.AgroAL/17

Unique identification code of the product type: [no DoP] - **termPIR AGRO AL** | d_N [20-250] | type of edges [FIT, LAP, TAG] - [modular length / width]

Manufacturer: GóR-Stal sp. z o.o., ul. Przemysłowa 11; 38-300 Gorlice, Poland / Place of manufacture: GóR-Stal; ul. Adolfa Mitey 9; 32-700 Bochnia, Poland

Harmonised standard: EN 13165:2012+A2:2016

The system/s of AVCP: System 3

Notified body/ies: Notified laboratory no **1488** (ITB, Warszawa, PL); **1454** (IMBiGS, Katowice, PL); **1487** (ICiMB, Kraków, PL)

Intended use/uses: thermal insulation products for buildings

Declared performances:

Essential characteristics	Performance	Values / classes					
Thermal resistance	Thickness tolerance, class	$(20 \leq d_N < 50 \text{ mm})$: $\pm 2 \text{ mm, T2}$		$(50 \leq d_N \leq 75 \text{ mm})$: $\pm 3 \text{ mm, T2}$		$(75 < d_N \leq 250 \text{ mm})$: $\pm 5/-3 \text{ mm, T2}$	
	Thermal conductivity, λ_D	$(20 \leq d_N \leq 250 \text{ mm})$: 0,022 [W/m·K]					
	Thermal resistance, R_D [m ² ·K/W]	20 mm: 0,90	30 mm: 1,35	40 mm: 1,85	50 mm: 2,30	60 mm: 2,75	70 mm: 3,25
		80 mm: 3,70	90 mm: 4,15	100 mm: 4,65	110 mm: 5,10	120 mm: 5,55	130 mm: 6,05
		140 mm: 6,50	150 mm: 6,95	160 mm: 7,45	170 mm: 7,90	180 mm: 8,35	190 mm: 8,85
		200 mm: 9,30	210 mm: 9,75	220 mm: 10,2	230 mm: 10,7	240 mm: 11,1	250 mm: 11,6
Reaction to fire (of the product as placed on the market)		Class E ($20 \leq d_N < 40 \text{ mm}$) Class D-s2,d0 ($40 \leq d_N \leq 250 \text{ mm}$)					
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of reaction to fire of the product as placed on the market	NPD; <i>The fire performance of PIR does not deteriorate with time (acc. EN 13165+A2)</i>					
Durability of thermal resistance against heat, weathering, ageing / degradation	Thermal conductivity, λ_D aged values	$(20 \leq d_N \leq 250 \text{ mm})$: 0,022 [W/m·K]					
	Thermal resistance, R_D [m ² ·K/W] aged values (for thickness d_N)	20 mm: 0,90	30 mm: 1,35	40 mm: 1,85	50 mm: 2,30	60 mm: 2,75	70 mm: 3,25
		80 mm: 3,70	90 mm: 4,15	100 mm: 4,65	110 mm: 5,10	120 mm: 5,55	130 mm: 6,05
		140 mm: 6,50	150 mm: 6,95	160 mm: 7,45	170 mm: 7,90	180 mm: 8,35	190 mm: 8,85
		200 mm: 9,30	210 mm: 9,75	220 mm: 10,2	230 mm: 10,7	240 mm: 11,1	250 mm: 11,6
	Durability characteristics	NPD					
Dimensional stability	$(20 \leq d_N < 50 \text{ mm})$: DS(70,-)1		$(50 \leq d_N \leq 250 \text{ mm})$: DS(-20,-)2 / DS(70,90)3				
Deformation under specified compressive load and temper. condition	NPD						
Compressive strength	Compressive stress, σ_{10}	NPD					
Tensile strength	Tensile strength perpendicular to faces	NPD					
Durability of compressive strength against ageing / degradation	Compressive creep	NPD					
Water permeability	Long term water absorption	$\leq 2 \%$ [kg/kg] / WL(T)2					
	Short term water absorption	NPD					
	Flatness after one-sided wetting	$\leq 10 \text{ mm}$ / FW2					
Water vapour permeability	Water vapour transmission, μ	NPD					
Acoustic absorption index	Sound absorption	NPD					
Release of dangerous substances to the indoor environment		NPD; <i>European test methods are under development for this characteristic.</i>					
Continuous glowing combustion		NPD; <i>European test methods are under development for this characteristic.</i>					

Harmonised standard: EN 13165:2012+A2:2016

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

"GÓR-STAL" Sp. z o.o.
 38-300 Gorlice, ul. Przemysłowa 11
 tel. 018 353 98 00
 REGON 852712117 NIP 738-19-45-154

GŁÓWNY TECHNOLOG

Bartłomiej Bochnia

Bochnia, 01.11.2024
 place and date of issue

signature and seal of the authorized person